D460SL

- 46″ Stand Alone
- Resolution 1360 x 768
- Brightness 700cd/㎡
- Contrast Ratio 2000:1

Display Panel	Screen size		46 inch Wide
	Active Display Area (mm)		1018.35 x 572.54 mm
	Number of Pixels		1366 x 768 (WUXGA)
	Viewing Angle (H/V)		178º/178º (CR≥10)
	Brightness		700cd/㎡
	Contrast Ratio		2000:1
	Bezel Size (U/D/L/R)(mm)		11/11/11.5/11.5
	Out Line Dimension (mm)		1047.4 x 600.6 x 59.3 mm
	Display Color		16.7 Million
	Life Time		50,000h average
Resolution (Max)	Monitor		1366 x 768
	DTV		1080i
Connectivity & Control	Input		VGA(15pin D-sub), HDMI, RS232C Composite(BNC), Component (BNC) PC/Composite/Component Audio
	Output		VGA(15pin D-sub), HDMI, Composite(BNC), Component(BNC), RS232C, Speaker(Ready)
	Auto Cooling System		Yes (2EA)
	Auto Power Control (DPMS)		Yes
Feature	Tempered Glass		Yes
	Touch Screen (IR multi-touch)		Option (D460SLI)
Power Requirement	Input Voltage		100 – 240 VAC
	Consumption (Watt)		260W
	DPMS (Watt)		2W
Mechanical	Dimension	Set (W x L x H)	701.8 x 500 x 1992 (H) mm
		Packed	840 x 660 x 2050 (H) mm
	Weight	Set	100kg
Approvals	EMI/EMC		FCC, CE
	Safety		cTUVus, TUV, CB
Accessory	Power cord, Manual, VGA Cable, Remocon, Audio Cable		
Temperature	0℃ - 40℃		
Humidity	20% - 80%		

HYUNDAI
HYUNDAI IT CORP.